

# *Appendix B*

## *2002 Environmental Monitoring Program*



*The WVDP Supports a Bluebird and Wood Duck Nesting-Box Program  
Sponsored by the Springville Field and Stream Club*

*This page intentionally left blank*

## ***2002 Environmental Monitoring Program***

The following schedule represents the West Valley Demonstration Project (WVDP) routine environmental monitoring program for 2002. This schedule met or exceeded the minimum program specifications needed to satisfy the requirements of DOE Order 5400.1. It also met the requirements of DOE Order 5400.5 and DOE/EH-0173T. Specific methods and recommended monitoring program elements are found in DOE/EP-0096, *A Guide for Effluent Radiological Measurements at DOE Installations*, and DOE/EP-0023, *A Guide for Environmental Radiological Surveillance at U.S. Department of Energy Installations*, which were the bases for selecting most of the schedule specifics. Additional monitoring was mandated by air and water discharge permits (40 CFR 61 and SPDES), which also required formal reports. Specifics are identified in the schedule under Monitoring/Reporting Requirements.

A computerized environmental data-screening system identifies analytical data that exceed pre-set limits. All locations are checked monthly for trends or notable results in accordance with criteria established in *Documentation and Reporting of Environmental Monitoring Data* (West Valley Nuclear Services Co., Inc., August 19, 1998). Reportable results are then described in a monthly trend analysis report together with possible causes and corrective actions, if indicated. A WVDP effluent summary report is transmitted with each monthly trend analysis report.

### ***Schedule of Environmental Sampling***

The index on pages B-v through B-vii is a list of the codes used to identify the various sampling locations, which are shown on Figures A-1 through A-13 (pp. A-3 through A-15 in Appendix A). The schedule of environmental sampling at the WVDP is found in this appendix on pages B-1 through B-47. Table headings in the schedule are as follows:

- ***Sample Location Code.*** Describes the physical location where the sample is collected. The code consists of seven or eight characters: The first character identifies the sample medium as **Air**, **Water**, **Soil/Sediment**, **Biological**, or **Direct Measurement**. The second character specifies **oN-site** or **oFf-site**. The remaining characters describe the specific location (e.g., **AFGRVAL** is **Air oFf-site** at **GR**eat **VAL**ley). Distances noted at sampling locations are as measured in a straight line from the main stack on-site.
- ***Monitoring/Reporting Requirements.*** Notes the bases for monitoring the location, any additional references to permits, and the reports that are generated from the sample data. Routine reports cited in this appendix are the Effluent Summary Report (ESR), the Monthly Trend Analysis Report (MTAR), the Air Emissions Report (NESHAP), and the Annual Site Environmental Report (ASER).
- ***Sampling Type/Medium.*** Describes the collection method and the physical characteristics of the medium.
- ***Collection Frequency.*** Indicates how often the samples are collected or retrieved.
- ***Total Annual Sample Collections.*** Specifies the number of discrete physical samples collected annually for each group of analytes.
- ***Analyses Performed/Composite Frequency.*** Notes the type of analyses of the samples taken at each collection, the frequency of composite, and the analytes determined for the composite samples.

## *Summary of Monitoring Program Changes in 2002*

<b>Location Code</b>	<b>Description of Changes</b>
ANLAUNV	Sampling at ANLAUNV was discontinued in August 2002 at DOE direction.
WNSP001	The updated SPDES permit for the site (July 2002) included the following analytical changes: analysis of two (2) 24-hour flow-weighted composite samples per discharge for total mercury using both EPA Methods 245.1 and 1669/1631 was added; quarterly analyses of 24-hour composite samples for bromide and boron was added; monitoring frequency for dichlorodifluoromethane and trichlorofluoromethane was changed from two grab samples per discharge to one grab sample per year.
WNSP01B	Per the July 2002 permit, point WNSP01B, an internal monitoring point for the liquid waste treatment system evaporator effluent, is being monitored for flow and for total mercury by the methods listed above for point WNSP001.

## ***Index of Environmental Monitoring Program Sample Points***

### **Air Effluent and On-Site Ambient Air (Fig. A-4 [p. A-6])**

ANSTACK	Main Plant	B-1
ANSTSTK	Supernatant Treatment System	B-1
ANCSSTK	01-14 Building	B-1
ANCSRFK	Size-Reduction Facility	B-1
ANCSPFK	Container Sorting and Packaging Facility	B-1
ANVITSK	Vitrification Heating, Ventilation, and Air Conditioning	B-1
ANSEISK	Seismic Sampler (Vitrification backup)	B-1
OVES/PVUs*	Outdoor Ventilated Enclosures/Portable Ventilation Units	B-3
ANLLW2V	Low-Level Waste Treatment Ventilation	B-5
ANLLWTVH**	Low-Level Waste Treatment Ventilation (radioactive operations)	B-5
ANLAUNV	Contaminated Clothing Laundry Ventilation	B-5
ANLAGAM	Lag Storage Area (ambient air)	B-5
ANNDAAAM	NDA Area (ambient air)	B-5
ANSDAT9	SDA Trench 9 (ambient air)	B-5

### **Liquid Effluent and On-Site Water (Fig. A-2 [p. A-4])**

WNSP001	Lagoon 3 Weir Point	B-7
WNSP01B*	Internal Process Monitoring Point	B-9
WNSP116	Pseudo-Monitoring Point Outfall 116	B-9
WNSP006	Facility Main Drainage	B-11
WNURRAW*	Utility Room Raw Water	B-11
WNSP007	Sanitary Waste Discharge	B-11
WNSWAMP	Northeast Swamp Drainage Point	B-13
WNSW74A	North Swamp Drainage Point	B-13
WNSDADR	SDA Run-Off	B-13
WNSP008	French Drain LLWTF Area	B-15
WNSP005	South Facility Drainage	B-15
WNCoolW	Cooling Tower	B-15
WNFRC67	Frank's Creek East	B-17
WNERB53	Erdman Brook	B-17
WNNDADR	Disposal Area Drainage	B-17
WNDCELD	Drum Cell Drainage	B-17
WNNDATR	NDA Trench Interceptor Project	B-17
WNSTAW Series	Standing Water	B-19
WNDNK Series*	Site Potable Water	B-21

\* Not detailed on map.

\*\* The location and sampler are no longer in use. Deletion of this sampling point is in progress. No samples were collected in 2002.

## ***Index of Environmental Monitoring Program Sample Points (continued)***

### **On-Site Groundwater and Seeps (Figs. A-6 through A-8 [pp. A-8 through A-10])**

SSWMU #1	Low-Level Waste Treatment Facility Wells	B-23
SSWMU #2	Miscellaneous Small Units Wells	B-23
SSWMU #3	Liquid Waste Treatment System Wells	B-23
SSWMU #4	HLW Storage and Processing Tank Wells	B-25
SSWMU #5	Maintenance Shop Leach Field Wells	B-25
SSWMU #6	Low-Level Waste Storage Area Wells	B-25
SSWMU #7	CPC Waste Storage Area Wells	B-25
SSWMU #8	CDDL Wells	B-27
SSWMU #9	NDA Units Wells and NDATR	B-27
SSWMU #10	IRTS Drum Cell Wells	B-27
SSWMU #11	SDA Unit Wells	B-29
North Plateau Seeps	Northeastern Edge of North Plateau	B-29
Well Points	Downgradient of Main Plant	B-29
WNWNB1S	Former North Plateau Background Well	B-29

### **Off-Site Surface Water (Fig. A-3 [p. A-5])**

WFBCTCB	Buttermilk Creek at Thomas Corners	B-31
WFFELBR	Cattaraugus Creek at Felton Bridge	B-31
WFBCKBG	Buttermilk Creek near Fox Valley (background)	B-31
WFBIGBR	Cattaraugus Creek at Bigelow Bridge (background)	B-31

### **Off-Site Drinking Water (Figs. A-9, A-12, and A-13 [pp. A-11, A-14, and A-15])**

WFWEL Series	Private Local Wells	B-33
--------------	---------------------	------

### **Off-Site Ambient Air (Figs. A-5, A-12, and A-13 [pp. A-7, A-14, and A-15])**

AFFXVRD	Fox Valley Sampler	B-35
AFTCORD	Thomas Corners Sampler	B-35
AFRT240	Route 240 Sampler	B-35
AFSPRVL	Springville Sampler	B-35
AFWEVAL	West Valley Sampler	B-35
AFNASHV	Nashville Sampler (background)	B-35
AFBOEHN	Dutch Hill Road Sampler	B-35
AFRSPRD	Rock Springs Road Sampler	B-35
AFGRVAL	Great Valley Sampler (background)	B-35
AFBLKST	Bulk Storage Warehouse Sampler	B-35

## ***Index of Environmental Monitoring Program Sample Points (concluded)***

### **Fallout, Sediment, and Soil (Figs. A-2 through A-5 [pp. A-4 through A-7], A-12, and A-13 [pp. A-14 and A-15])**

AFDHFOP	Dutch Hill Fallout	B-37
AFFXFOP	Fox Valley Fallout	B-37
AFTCFOP	Thomas Corners Fallout	B-37
AF24FOP	Route 240 Fallout	B-37
ANRGFOP	Rain Gauge Fallout	B-37
SF Soil Series	Air Sampler Area Soil	B-37
SFCCSED	Cattaraugus Creek at Felton Bridge, Sediment	B-37
SFSDSED	Cattaraugus Creek at Springville Dam, Sediment	B-37
SFBISED	Cattaraugus Creek at Bigelow Bridge, Background Sediment	B-37
SFTCSSED	Buttermilk Creek at Thomas Corners, Sediment	B-37
SFBCSED	Buttermilk Creek at Fox Valley Road, Background Sediment	B-37
SN Soil Series:	On-Site Soils/Sediments	B-37
SNSW74A		B-37
SNSWAMP		B-37
SNSP006		B-37

### **Off-Site Biological (Figs. A-9, A-12, and A-13 [pp. A-11, A-14, and A-15])**

BFFCATC	Cattaraugus Creek Fish, Downstream	B-39
BFFCATD	Cattaraugus Creek Fish, Downstream of Springville Dam	B-39
BFFCTRL	Cattaraugus Creek Fish, Background	B-39
BFMREED	NNW Milk	B-39
BFMCTLS	Milk, South, Background	B-39
BFMCTLN	Milk, North, Background	B-39
BFMWIDR	Southeast Milk, Near-Site	B-39
BFMSCHT	South Milk, Near-Site	B-39
BFVNEAR*	Produce, Near-Site	B-41
BFVCTRL*	Produce, Background	B-41
BFHNEAR	Forage, Near-Site	B-41
BFHCTLS	Forage, South, Background	B-41
BFHCTLN	Forage, North, Background	B-41
BFBNEAR	Beef, Near-Site	B-41
BFBCTRL	Beef, Background	B-41
BFDNEAR	Venison, Near-Site	B-41
BFDCCTRL	Venison, Background	B-41

### **Direct Measurement Dosimetry (Figs. A-10 through A-13 [pp. A-12 through A-15])**

DFTLD Series	Off-Site Direct Radiation	B-43
DNTLD Series	On-Site Direct Radiation	B-45

\* Near-site and background produce samples (corn, apples, and beans) are identified specifically as follows: corn = **BFVNEAC** and **BFVCTRC**; apples = **BFVNEAAF** and **BFVCTRA**; beans = **BFVNEAB** and **BFVCTRB**.

## 2002 Monitoring Program On-Site Effluent Monitoring

### Air Effluents

Sample Location Code	Monitoring/Reporting Requirements	Sampling Type/Medium	Collection Frequency	Total Annual Sample Collections	Analyses Performed/ Composite Frequency
<b>ANSTACK</b> <i>Main Plant Ventilation Exhaust Stack</i>	Airborne radioactive effluent points, including the LWTS and vitrification off-gas  Required by: <ul style="list-style-type: none"> <li>• 40 CFR 61</li> </ul> Reported in: <ul style="list-style-type: none"> <li>• ESR</li> <li>• MTAR</li> <li>• ASER</li> <li>• Air Emissions Annual Report (NESHAP)</li> </ul>	Continuous off-line air particulate monitors	→ Continuous measurement of fixed filter; replaced weekly	→ NA	→ Real-time alpha and beta monitoring
<b>ANSTSTK</b> <i>Supernatant Treatment System (STS) Ventilation Exhaust</i>		Continuous off-line air particulate filters	→ Weekly	→ 52 each location	→ Gross alpha/beta, gamma isotopic* upon collection, flow
<b>ANCSSTK</b> <i>01-14 Building Ventilation Exhaust</i>		Weekly filters composited to 4 each location	→	→	→ Quarterly composites for Sr-90, U-232, U-233/234, U-235/236, U-238, total U, Pu-238, Pu-239/240, Am-241, gamma isotopic
<b>ANCSRFK</b> <i>Contact Size-Reduction Facility Exhaust</i>		Continuous off-line desiccant columns for water vapor collection	→ Weekly	→ 52 at each of two locations	→ H-3 ( <b>ANSTACK</b> and <b>ANSTSTK</b> only)
<b>ANCSPFK</b> <i>Container Sorting and Packaging Facility Exhaust</i>		Continuous off-line charcoal cartridges	→ Weekly	→ Weekly cartridges composited to 4 each location	→ Quarterly composite for I-129
<b>ANVITSK</b> <i>Vitrification HVAC Exhaust</i>					
<b>ANSEISK</b> <i>Seismic Sampler, Vitrification Backup</i>	Airborne radioactive effluent point  Required by: <ul style="list-style-type: none"> <li>• 40 CFR 61</li> </ul> Reported in: <ul style="list-style-type: none"> <li>• ESR</li> <li>• MTAR</li> <li>• ASER</li> </ul>	Continuous off-line air particulate filter	→ Weekly	→ 52	→ Filters for gross alpha/beta, gamma isotopic* upon collection, flow

\* Weekly gamma isotopic only if gross activity rises significantly.  
NA - Not applicable.



## Sampling Rationale

---

<b>ANSTACK</b>	DOE/EH-0173T, 3.0; DOE/EP-0096, 3.3  Monitors and samples HEPA-filtered ventilation from most process areas, including cell ventilation, vessel off-gas, fuel receiving and storage (FRS), head end ventilation, and an analytical aisle. Requires continuous effluent monitoring per 40 CFR Subpart H, Section 61.93(b) because potential emissions may exceed the 0.1 mrem limit.
<b>ANSTSTK</b>	DOE/EH-0173T, 3.0; DOE/EP-0096, 3.3  Monitors and samples HEPA-filtered ventilation (permanent ventilation system [PVS]) from building areas involved in treatment of high-level waste supernatant. Requires continuous effluent monitoring per 40 CFR Subpart H, Section 61.93(b) because potential emissions may exceed the 0.1 mrem limit.
<b>ANCSSTK</b>	DOE/EH-0173T, 3.0; DOE-EP-0096, 3.3  Monitors and samples HEPA-filtered ventilation from the 01-14 building, which houses equipment used to treat the ceramic melter off-gas. Requires effluent monitoring per 40 CFR Subpart H, Section 61.93(b) to confirm that emissions are less than the 0.1 mrem limit.
<b>ANCSRFK</b>	DOE/EH-0173T, 3.0; DOE-EP-0096, 3.3  Monitors and samples HEPA-filtered ventilation from a process area where radioactive tanks, pipes, and other equipment are cut up with a plasma torch to reduce volume.
<b>ANCSPFK</b>	DOE/EH-0173T, 3.0; DOE-EP-0096, 3.3  Monitors and samples ventilation from lag storage area 4, the container sorting and packaging facility.
<b>ANVITSK</b>	DOE/EH-0173T, 3.0; DOE-EP-0096, 3.3  Vitrification facility heating, ventilation, and air conditioning (HVAC) effluent exhaust stack. Sampler brought on-line in late 1995 when nonradioactive operations began. Radioactive operation began with the first high-level waste transfer in June 1996 and vitrification startup in July 1996. Monitors and samples HEPA-filtered ventilation from building areas involved in treatment of high-level waste supernatant. Requires effluent monitoring per 40 CFR Subpart H, Section 61.93(b) because potential emissions may exceed the 0.1 mrem limit.
<b>ANSEISK</b>	DOE/EH-0173T, 3.0; DOE-EP-0096, 3.3  Vitrification system back-up filter for catastrophic-event monitoring in case the primary vitrification HVAC stack ventilation fails.

- Sampling locations are shown on Figure A-4 (p. A-6).

**2002 Monitoring Program  
On-Site Effluent Monitoring**

**Air Effluents**

<u>Sample Location Code</u>	<u>Monitoring/Reporting Requirements</u>	<u>Sampling Type/Medium</u>	<u>Collection Frequency</u>	<u>Total Annual Sample Collections</u>	<u>Analyses Performed/ Composite Frequency</u>
<b>OVes/PVUs</b> <i>Outdoor Ventilated Enclosures/Portable Ventilation Units</i>	Airborne radioactive effluent points  Required by: <ul style="list-style-type: none"> <li>• 40 CFR 61</li> </ul> Reported in: <ul style="list-style-type: none"> <li>• ESR</li> <li>• MTAR</li> <li>• ASER</li> <li>• Air Emissions Annual Report (NESHAP)</li> </ul>	Continuous off-line air particulate filter	→ As required	→ 1 each location	→ Filters for gross alpha/beta, gamma isotopic* upon collection, flow
	Collected filters** composited to 4			→ Quarterly composites for Sr-90, U-232, U-233/234, U-235/236, U-238, total U, Pu-238, Pu-239/240, Am-241, gamma isotopic	

\* Gamma isotopic only if gross activity rises significantly.

\*\* If gross determination of individual filter is significantly higher than background, the individual sample would be submitted immediately for isotopic analysis.

## Sampling Rationale

---

**OVes/PVUs** DOE/EH-0173T, 3.0; DOE/EP-0096, 3.3

Outdoor ventilated enclosures; portable ventilation units used for handling radioactive materials or for decontamination in areas not having containment ventilation. Emissions are monitored to confirm that they are below the 0.1 mrem limit.

■ Sampling locations are not shown on figures.

**2002 Monitoring Program  
On-Site Effluent Monitoring**

**Air Effluents and On-Site Ambient Air**

Sample Location Code	Monitoring/Reporting Requirements	Sampling Type/Medium	Collection Frequency	Total Annual Sample Collections	Analyses Performed/Composite Frequency
<b>ANLLW2V</b> <i>Low-Level Waste Treatment and Ventilation (New Facility)</i>  <b>ANLLWTVH</b> <i>Low-Level Waste Treatment and Ventilation, "Hot" Side (Former Facility)</i>  <b>ANLAUNV</b> <i>Laundry Change Room Ventilation</i>	Airborne radioactive effluent point  Required by: <ul style="list-style-type: none"> <li>• 40 CFR 61</li> </ul> Reported in: <ul style="list-style-type: none"> <li>• ESR</li> <li>• MTAR</li> <li>• ASER</li> <li>• Air Emissions Annual Report (NESHAP)</li> </ul>	Continuous off-line air particulate filter   No samples were collected at <b>ANLLWTVH</b> in 2002  Continuous off-line air particulate filter	→ Quarterly →   → Monthly →	→ 4   → 12	→ Gross alpha/beta, gamma isotopic* upon collection, flow   → Gross alpha/beta, gamma isotopic* upon collection, flow
<b>ANLAGAM</b> <i>Lag Storage Area Ambient Air</i>  <b>ANNDAAAM</b> <i>NDA Ambient Air</i>	Ambient "diffuse source" air emissions  Reported in: <ul style="list-style-type: none"> <li>• MTAR</li> <li>• ASER</li> <li>• Air Emissions Annual Report (NESHAP)</li> </ul>	Continuous air particulate filter	→ Weekly →	→ 52 each location  Weekly filter composited to 4 each location	→ Gross alpha/beta, flow  → Quarterly composites for Sr-90, U-232, U-233/234, U-235/236, U-238, total U, Pu-238, Pu-239/240, Am-241, gamma isotopic
<b>ANSDAT9**</b> <i>SDA Trench 9 Ambient Air</i>	Ambient "diffuse source" air emissions  Reported in: <ul style="list-style-type: none"> <li>• MTAR</li> <li>• ASER</li> <li>• Reported to NYSERDA</li> </ul>	Continuous air particulate filter  Continuous off-line desiccant columns for water vapor collection  Continuous off-line charcoal cartridges	→ Weekly →  → Weekly →  → Monthly →	→ 52  Weekly filter composited to 4  → 52  Monthly cartridges composited to 4	→ Gross alpha/beta, flow  → Quarterly composite for gamma isotopic  → H-3  → Quarterly composite for I-129

\* Gamma isotopic only if gross activity rises significantly.

\*\* Sampling frequency and analytical parameters as directed by NYSERDA.

## Sampling Rationale

---

<b>ANLLW2V</b>	DOE/EH-0173T, 3.0; DOE/EP-0096, 3.3  Samples ventilation exhaust from the new low-level waste treatment facility. System started up in April 1998.
<b>ANLLWTVH</b>	DOE/EH-0173T, 3.0; DOE/EP-0096, 3.3  Decontamination and decommissioning activities are no longer being conducted in the former low-level waste treatment building. The building ventilation has been shut down and its sampler is currently inactive. No samples have been collected since CY 2000.
<b>ANLAUNV</b>	DOE/EH-0173T, 3.0; DOE/EP-0096, 3.3  Sampling was discontinued on 8/28/02.
<b>ANLAGAM</b>	DOE/EH-0173T, 3.3.2  Monitors ambient air in the lag storage area, a possible diffuse source of air emissions.
<b>ANNDAAAM</b>	DOE/EH-0173T, 3.3.2  Monitors ambient air in the NDA area, a possible diffuse source of air emissions.
<b>ANSDAT9</b>	DOE/EH-0173T, 3.3.2  Monitors potential diffuse sources of air emissions at the SDA and south plateau area. WVDP support of NYSERDA.

- Sampling locations are shown on Figure A-4 (p. A-6).

**2002 Monitoring Program  
On-Site Effluent Monitoring**

**Liquid Effluents**

Sample Location Code	Monitoring/Reporting Requirements	Sampling Type/Medium	Collection Frequency	Total Annual Sample Collections	Analyses Performed/ Composite Frequency
<b>WNXP001</b> <i>Lagoon 3 Discharge Weir</i>	Primary point of liquid effluent batch release  Required by: <ul style="list-style-type: none"> <li>• SPDES permit</li> </ul> Reported in: <ul style="list-style-type: none"> <li>• Monthly SPDES DMR</li> <li>• ESR</li> <li>• MTAR</li> <li>• ASER</li> </ul>	Grab liquid →	Daily, during lagoon 3 discharge*	24-56 →	Daily for gross beta, conductivity, flow
				4-10 →	Every 6 days a sample is analyzed for gross alpha/beta, H-3, Sr-90, gamma isotopic
				Composite of daily samples for each discharge, 4-8 →	Weighted composite for gross alpha/beta, H-3, C-14, Sr-90, Tc-99, I-129, gamma isotopic, U-232, U-233/234, U-235/236, U-238, total U, Pu-238, Pu-239/240, and Am-241 for each month of discharge
		Composite liquid →	Twice during discharge, near start and near end	8-16 →	Two 24-hour composites for BOD <sub>5</sub> , suspended solids, SO <sub>4</sub> , NO <sub>3</sub> , NO <sub>2</sub> , NH <sub>3</sub> , total Al, Fe, Hg, and Mn, total recoverable Cd, Cr, Cu, Ni, Pb, and Zn, dissolved As and Cu, dissolved sulfide
		Grab liquid →	Twice during discharge, near start and near end	8-16 →	Settleable solids, total dissolved solids, pH, cyanide amenable to chlorination, oil & grease, surfactant (as LAS), total recoverable Co, Cr <sup>+6</sup> , Se, and V, 3,3-dichlorobenzidine, tributyl phosphate, hexachlorobenzene, alpha-BHC, heptachlor, xylene, 2-butanone
		Composite liquid →	Semiannual	2 →	A 24-hour composite for titanium
		Composite liquid →	Annual	1 →	A 24-hour composite for Ba and Sb
		Grab liquid →	Semiannual	2 →	Bis(2-ethylhexyl) phthalate, 4-dodecene
		Grab liquid →	Annual	1 →	Chloroform, dichlorodifluoromethane, and trichlorofluoromethane
		Composite liquid →	Quarterly	4 →	Bromide and boron

\* Lagoon 3 is discharged four to eight times per year, as necessary, averaging six to seven days per discharge.

## Sampling Rationale

---

**WNSP001** DOE Order 5400.5; DOE/EH-0173T, 2.3.3; SPDES permit no. NY0000973

By DOE Order all liquid effluent streams from DOE facilities shall be evaluated and their potential for release of radionuclides addressed.

These requirements for radiological parameters are met by daily grab sampling during periods of lagoon 3 discharge. Sampling for chemical constituents is performed near the beginning and end of each discharge period to meet the site SPDES permit. Both grab samples and 24-hour composite samples are collected. Modifications to the SPDES permit on July 15, 2002 changed sampling frequency of dichlorodifluoromethane and trichlorofluoromethane from twice during discharge to annual grab. The permit added action sampling for bromide and boron on a quarterly basis.

■ Sampling location is shown on Figure A-2 (p. A-4).

**2002 Monitoring Program  
On-Site Effluent Monitoring**

**Liquid Effluents**

Sample Location Code	Monitoring/Reporting Requirements	Sampling Type/Medium	Collection Frequency	Total Annual Sample Collections	Analyses Performed/ Composite Frequency
<b>WNSP01B</b> <i>Internal Process Monitoring Point</i>	Internal point for monitoring Hg at effluent of the Hg pretreatment process  Required by: <ul style="list-style-type: none"> <li>• SPDES Permit</li> </ul> Reported in: <ul style="list-style-type: none"> <li>• Monthly SPDES DMR</li> </ul>	Continuous	→ Weekly	→ N/A	→ Flow
		Composite liquid	→ Twice per month when operating	→ 24	→ Total Hg
<b>WNSP116</b> <i>Pseudo-Monitoring Point Outfall 116</i>	Calculated concentration of dissolved solids at pseudo-monitoring point in Frank's Creek. Based upon TDS at WNSP001, WNSP006, and augmentation water.  Required by: <ul style="list-style-type: none"> <li>• SPDES Permit</li> </ul> Reported in: <ul style="list-style-type: none"> <li>• Monthly SPDES DMR</li> </ul>	Calculated	→ Twice per discharge event	→ 8-16	→ Total dissolved solids



## Sampling Rationale

---

**WNSP01B**      New York State SPDES permit no. NY0000973

This internal point is used to monitor mercury in effluent from the proposed mercury pretreatment process. Effluent from this point is subsequently released to lagoon 3, which is monitored at point WNSP001.

For permit requirements, total Hg is analyzed by U.S. EPA method 245.1. For mercury studies, samples will be analyzed by EPA method 1631.

**WNSP116**      New York State SPDES permit no. NY0000973

This “pseudo-monitoring point,” assumed to be in Frank’s Creek, is calculated from actual total dissolved solids (TDS) measurements and flow measurements from points WNSP001 and WNSP006 and from augmentation water.

■      Sampling location WNSP116 is shown on Figure A-2 (p. A-4). Sampling location WNSP01B is not shown on the figures.

**2002 Monitoring Program  
On-Site Effluent Monitoring**

**Liquid Effluents**

Sample Location Code	Monitoring/Reporting Requirements	Sampling Type/Medium	Collection Frequency	Total Annual Sample Collections	Analyses Performed/ Composite Frequency
<b>WNSP006</b> <i>Frank's Creek at the Security Fence</i>	Combined facility liquid discharge  Required by: <ul style="list-style-type: none"> <li>• SPDES Permit</li> </ul> Reported in: <ul style="list-style-type: none"> <li>• Monthly SPDES DMR</li> <li>• MTAR</li> <li>• ASER</li> </ul>	Timed continuous composite liquid	→ Weekly →	52  Weekly samples composited to 12  Weekly samples composited to 4	→ Gross alpha/beta, H-3, pH, conductivity → Monthly composite for gamma isotopic and Sr-90 (shared with NYSDOH) → Quarterly composite for C-14, Tc-99, I-129, U-232, U-233/234, U-235/236, U-238, total U, Pu-238, Pu-239/240, Am-241
		Grab liquid	→ Twice during discharge, near start and near end →	8-16	→ TDS
		Grab liquid	→ Semiannual →	2	→ NPOC, TOX, Ca, Mg, Na, K, Ba, Mn, Fe, Cl, SO <sub>4</sub> , NO <sub>3</sub> +NO <sub>2</sub> -N, F, HCO <sub>3</sub> , CO <sub>3</sub>
<b>WNURRAW</b> <i>Utility Room Raw Water</i>	Source water  Required by: <ul style="list-style-type: none"> <li>• SPDES Permit</li> </ul> Reported in: <ul style="list-style-type: none"> <li>• Monthly SPDES DMR</li> </ul>	Grab liquid	→ Weekly →	52	→ Total Fe
		Grab liquid	→ Twice during discharge, near start and near end →	8-16	→ TDS
<b>WNSP007</b> <i>Sanitary Waste Discharge</i>	Liquid effluent point for sanitary and utility plant combined discharge  Required by: <ul style="list-style-type: none"> <li>• SPDES Permit</li> </ul> Reported in: <ul style="list-style-type: none"> <li>• Monthly SPDES DMR</li> <li>• ESR</li> <li>• MTAR</li> <li>• ASER</li> </ul>	24-hour composite liquid	→ 3 each month →	36  Monthly samples composited to 4	→ Gross alpha/beta, H-3, pH, suspended solids, NH <sub>3</sub> , NO <sub>2</sub> -N, BOD <sub>5</sub> , total Fe → Quarterly composite for gamma isotopic
		Grab liquid	→ 3 each month →	36	→ Oil & grease
		Grab liquid	→ Weekly →	52	→ pH, settleable solids, total residual chlorine
		Grab liquid	→ Annual →	1	→ Chloroform

## Sampling Rationale

---

**WNSP006** DOE/EH-0173T, 5.10.1.1; SPDES permit no. NY0000973

By DOE Order all liquid effluent streams from DOE facilities shall be evaluated and their potential for release of radionuclides addressed.

In accordance with the WVDP SPDES permit no. NY0000973, outfall 116 (pseudo-monitoring point) uses flow data from **WNSP006**. Flow augmentation parameters (flow and total dissolved solids [TDS]) are monitored at location **WNSP006**; calculated TDS and flow data related to sample point **WNSP006** are reported for pseudo-monitoring point 116 in the monthly SPDES Discharge Monitoring Report (DMR).

**WNURRAW** SPDES permit no. NY0000973

TDS is measured near the beginning and end of each lagoon 3 discharge. Results are used for outfall 116 calculations. (See **WNSP006** above.)

**WNSP007** DOE Order 5400.5; DOE/EH-0173T, 2.3.3

Sampling rationale is based on New York State SPDES permit no. NY0000973 and DOE Order 5400.5 criteria.

- Sampling locations WNSP006 and WNSP007 are shown on Figure A-2 (p. A-4). Sampling location WNURRAW is not shown on the figures.

**2002 Monitoring Program  
Environmental Surveillance**

**On-Site Surface Water**

Sample Location Code	Monitoring/Reporting Requirements	Sampling Type/Medium	Collection Frequency	Total Annual Sample Collections	Analyses Performed/ Composite Frequency
<b>WNSWAMP</b> <i>Northeast Swamp Drainage</i>	Site surface drainage  Reported in: • ESR • MTAR • ASER	Timed continuous composite liquid	→ Weekly	→ 52	→ Gross alpha/beta, H-3, pH, conductivity  Weekly samples composited to 12 → Monthly composite for gamma isotopic and Sr-90 (shared with NYSDOH)  Weekly samples composited to 4 → Quarterly composite for C-14, I-129, U-232, U-233/234, U-235/236, U-238, total U, Pu-238, Pu-239/240, Am-241
		Grab liquid	→ Semiannual	→ 2	→ NPOC, TOX, Ca, Mg, Na, K, Ba, Mn, Fe, Cl, SO <sub>4</sub> , NO <sub>3</sub> +NO <sub>2</sub> -N, F, HCO <sub>3</sub> , CO <sub>3</sub>
<b>WNSW74A</b> <i>North Swamp Drainage</i>	Site surface drainage  Reported in: • ESR • MTAR • ASER	Timed continuous composite liquid	→ Weekly	→ 52	→ Gross alpha/beta, H-3, pH, conductivity  Weekly samples composited to 12 → Monthly composite for gamma isotopic and Sr-90  Weekly samples composited to 4 → Quarterly composite for C-14, I-129, U-232, U-233/234, U-235/236, U-238, total U, Pu-238, Pu-239/240, Am-241
		Grab liquid	→ Semiannual	→ 2	→ NPOC, TOX, Ca, Mg, Na, K, Ba, Mn, Fe, Cl, SO <sub>4</sub> , NO <sub>3</sub> +NO <sub>2</sub> -N, F, HCO <sub>3</sub> , CO <sub>3</sub>
<b>WNSDADR</b> <i>SDA Run-Off</i>	Surface water run-off from south portion of SDA  Required by: • Interim Measures Compliance  Reported in: • MTAR • ASER • Reported to NYSERDA	Grab liquid	→ Monthly	→ 12 maximum	→ pH, total suspended solids, oil & grease, flow, gross alpha/beta, H-3, gamma isotopic

## Sampling Rationale

---

**WNSWAMP**      DOE/EH-0173T, 5.10.1.1

Northeast site surface water drainage; provides for sampling of uncontrolled surface waters from this discrete drainage path just before they leave the site's controlled boundary. Waters represent surface and subsurface drainages from the construction and demolition debris landfill (CDDL), old hardstand areas, and other possible north plateau sources of radiological or nonradiological contamination including the strontium-90 groundwater plume.

**WNSW74A**      DOE/EH-0173T, 5.10.1.1

North site surface water drainage; provides for sampling of uncontrolled surface waters from this discrete drainage path just before they leave the site's controlled boundary. Waters represent surface and subsurface drainages from lag storage areas and other possible north plateau sources of radiological or nonradiological contamination.

**WNSDADR**      NYSERDA interim measures compliance.

■      Sampling locations are shown on Figure A-2 (p. A-4).

**2002 Monitoring Program  
Environmental Surveillance**

**On-Site Surface Water**

<u>Sample Location Code</u>	<u>Monitoring/Reporting Requirements</u>	<u>Sampling Type/Medium</u>	<u>Collection Frequency</u>	<u>Total Annual Sample Collections</u>	<u>Analyses Performed/ Composite Frequency</u>
<b>WNSP008</b> <i>French Drain</i>	Drains subsurface water from LLWTF lagoon area  Required by: <ul style="list-style-type: none"> <li>• SPDES Permit</li> </ul> Reported in: <ul style="list-style-type: none"> <li>• Monthly SPDES DMR</li> <li>• ESR</li> <li>• MTAR</li> <li>• ASER</li> </ul>	Grab liquid	→ Monthly	→ 12	→ Gross alpha/beta, H-3
		Grab liquid	→ 3 each month	→ 36	→ Conductivity, pH, BOD <sub>5</sub> , total Fe, total recoverable Cd, and Pb
		Grab liquid	→ Annual	→ 1	→ As, Cr, total Ag, and Zn
<b>WNSP005</b> <i>Facility Yard Drainage</i>	Combined drainage from facility yard area  Reported in: <ul style="list-style-type: none"> <li>• MTAR</li> <li>• ASER</li> </ul>	Grab liquid	→ Monthly	→ 12	→ Gross alpha/beta, H-3, pH
<b>WNCOOLW</b> <i>Cooling Tower Basin</i>	Cools plant utility steam system water  Reported in: <ul style="list-style-type: none"> <li>• MTAR</li> <li>• ASER</li> </ul>	Grab liquid	→ Monthly	→ 12	→ Gross alpha/beta, H-3, pH
				Monthly samples composited to 4	→ Quarterly composite for gamma isotopic

## Sampling Rationale

---

- WNSP008** DOE/EH-0173T, 5.10.1.3; SPDES permit no. NY0000973.
- French drain of subsurface water from lagoon (LLWTF) area. The SPDES permit also provides for sampling of uncontrolled subsurface water from this discrete drainage path before these waters flow into Erdman Brook. Waters represent subsurface drainages from downward infiltration around the LLWTF and lagoon systems. This point would also monitor any subsurface spillover from the overflowing of lagoons 2 and 3. Sampling is of significance for both radiological and nonradiological contamination. This point was capped off in May 2001.
- WNSP005** Facility yard surface water drainage; generally in accordance with DOE/EH-0173T, 5.10.1.1. Previously in accordance with SPDES permit no. NY0000973.
- Provides for the sampling of uncontrolled surface waters from this discrete drainage path after outfall 007 discharge into the drainage and before these waters flow into Erdman Brook. Waters represent surface and subsurface drainages primarily from the main plant yard area. Historically, this point was used to monitor sludge pond and utility room discharges to the drainage. These two sources have been rerouted. Migration of residual site contamination around the main plant dictates surveillance of this point, primarily for radiological parameters.
- WNC00LW** Facility cooling tower circulation water; generally in accordance with DOE/EH-0173T, 5.10.1.1.
- Operational sampling carried out to confirm that radiological contamination is not migrating into the primary coolant loop of the high-level waste treatment facility and/or plant utility steam systems. Migration from either source might indicate radiological control failure.

- Sampling locations are shown on Figure A-2 (p. A-4).

**2002 Monitoring Program  
Environmental Surveillance**

**On-Site Surface Water**

Sample Location Code	Monitoring/Reporting Requirements	Sampling Type/Medium	Collection Frequency	Total Annual Sample Collections	Analyses Performed/Composite Frequency
<b>WNFRC67*</b> <i>Frank's Creek East of the SDA</i>	Drains NYS Low-level Waste Disposal Area  Reported in: • MTAR • ASER • Reported to NYSERDA	Grab liquid	→ Monthly	→ 12	→ Gross alpha/beta, H-3, pH
<b>WNERB53*</b> <i>Erdman Brook North of Disposal Areas</i>	Drains NYS and WVDP disposal areas  Reported in: • MTAR • ASER • Reported to NYSERDA	Grab liquid	→ Weekly	→ 52	→ Gross alpha/beta, H-3, pH
<b>WNNDADR</b> <i>Drainage Between NDA and SDA</i>	Drains WVDP disposal and storage area  Reported in: • MTAR • ASER • Reported to NYSERDA	Timed continuous composite liquid	→ Weekly	→ 52	→ pH
				Weekly samples composited to 12	→ Monthly composite for gross alpha/beta, gamma isotopic, H-3
				Weekly samples composited to 4	→ Quarterly composite for Sr-90, I-129
<b>WNDCELD</b> <i>Drainage South of Drum Cell</i>	Drains WVDP storage area  Reported in: • MTAR • ASER • Reported to NYSERDA	Grab liquid	→ Monthly	→ 12	→ pH, gross alpha/beta
				Monthly samples composited to 4	→ Quarterly composite for H-3, Sr-90, I-129, gamma isotopic
<b>WNNDATR**</b> <i>NDA Trench Interceptor Project</i>	On-site groundwater interception  Reported in: • MTAR • ASER	Grab liquid	→ Monthly	→ 12	→ Gross alpha/beta, H-3, gamma isotopic, NPOC, TOX
				Monthly samples composited to 4	→ Quarterly composite for I-129

\* Monthly sample also collected by NYSDOH

\*\* Coordinated with Main Plant Operations



## Sampling Rationale

---

<b>WNFRC67</b>	DOE/EH-0173T, 5.10.1.1  Monitors the potential influence of both the SDA and drum cell drainage into Frank's Creek east of the SDA and upstream of its confluence with Erdman Brook.
<b>WNERB53</b>	DOE/EH-0173T, 5.10.1.1  Monitors the potential influence of the drainages from the SDA and the WVDP storage and disposal area into Erdman Brook upstream of its confluence with Frank's Creek.
<b>WNNDADR</b>	DOE/EH-0173T, 5.10.1.1  Monitors the potential influence of the drainages from the SDA and the WVDP storage and disposal area into Lagoon Road Creek upstream of the creek's confluence with Erdman Brook.
<b>WNDCELD</b>	DOE/EH-0173T, 5.10.1.1  Monitors the potential influence of drum cell drainage into Frank's Creek south of the SDA and upstream of <b>WNFRC67</b> .
<b>WNNDATR</b>	DOE Order 5400.1, IV.9  Monitors groundwater in the vicinity of the NDA interceptor trench project. The grab sample is taken directly from the trench collection system.

- Sampling locations are shown on Figure A-2 (p. A-4).

**2002 Monitoring Program  
Environmental Surveillance**

**On-Site Surface Water**

<u>Sample Location Code</u>	<u>Monitoring/Reporting Requirements</u>	<u>Sampling Type/Medium</u>	<u>Collection Frequency</u>	<u>Total Annual Sample Collections</u>	<u>Analyses Performed/ Composite Frequency</u>
<b>WNSTAW Series</b> <i>On-Site Standing Water Ponds Not Receiving Effluent</i>  <b>WNSTAW4</b> <i>Border Pond Southwest of AFRT240</i>  <b>WNSTAW5</b> <i>Border Pond Southwest of DFTLD13</i>  <b>WNSTAW6</b> <i>Borrow Pit Northeast of Project Facilities</i>  <b>WNSTAW9</b> <i>North Reservoir Near Intake</i>  <b>WNSTAWB</b> <i>Background Pond at Sprague Brook Maintenance Building</i>	Water within vicinity of airborne or water effluent from the plant  Reported in: <ul style="list-style-type: none"> <li>• MTAR</li> <li>• ASER</li> </ul>	Grab liquid	→ Annual	→ 1 each location*	→ Gross alpha/beta, H-3, pH, conductivity, Cl, Fe, Mn, Na, NO <sub>3</sub> +NO <sub>2</sub> -N, SO <sub>4</sub>

\* Sampling depends upon on-site ponding conditions during the year.

## Sampling Rationale

---

**WNSTAW Series** DOE/EH-0173T, 5.10.1.1

Monitoring of on- and off-site standing waters at locations listed below. Although none receive effluent directly, the potential for contamination is present except at the background location. Former collecting sites 1,2,3,7, and 8 were deleted from the monitoring program because they were either built over or are now dry.

**WNSTAW4** Border pond located south of **AFRT240**. Chosen as a location for showing potentially high concentrations, based on meteorological data. This perimeter location is next to a working farm. Drainage extends through private property and is accessible by the public.

**WNSTAW5** Border pond located west of Project facilities near the perimeter fence and **DFTL13**. Chosen as a location for showing potentially high concentrations, based on meteorological data. Location is next to a private residence and potentially accessible by the general public.

**WNSTAW6** Borrow pit northeast of Project facilities just outside the inner security fence. Considered the closest standing water to the main plant and high-level waste facilities.

**WNSTAW9** North reservoir near intake. Chosen to provide data in the event of potentially contaminated site potable water supply. Location is south of main plant facilities.

**WNSTAWB** Pond located near the Sprague Brook maintenance building. Considered a background location; approximately 14 kilometers north of the WVDP.

■ Sampling locations are shown on Figures A-2, A-3, and A-13 (pp. A-4, A-5, and A-15).

**2002 Monitoring Program  
Environmental Surveillance**

**On-Site Potable Water**

<u>Sample Location Code</u>	<u>Monitoring/Reporting Requirements</u>	<u>Sampling Type/Medium</u>	<u>Collection Frequency</u>	<u>Total Annual Sample Collections</u>	<u>Analyses Performed/ Composite Frequency</u>
<b>WNDNK Series</b> <i>Site Potable Water</i>  <b>WNDNKMS</b> <i>Maintenance Shop Drinking Water</i>  <b>WNDNKMP</b> <i>Main Plant Drinking Water</i>  <b>WNDNKEL</b> <i>Environmental Laboratory Drinking Water</i>  <b>WNDNKUR</b> <i>Utility Room (EP-1) Potable Water Storage Tank</i>	Sources of potable water within site perimeter  Reported in:  <ul style="list-style-type: none"> <li>• MTAR</li> <li>• ASER</li> <li>• Also reported to Cattaraugus County</li> </ul>	Grab liquid →  Grab liquid* →	Monthly →  Annual →	12 per location →  1 →	→ Gross alpha/beta, H-3, pH, conductivity  → As, Ba, Be, Cd, Cr, Hg, Ni, Sb, Se, Tl, cyanide, fluoride

\* **WNDNKUR** only. Sample for NO<sub>3</sub> (as total nitrate) is collected by the Cattaraugus County Health Department. Pb and Cu also are sampled at this site based upon Cattaraugus County Health Department guidance.

## Sampling Rationale

---

- WNDNK Series** Site drinking water; generally according to DOE/EH-0173T, 5.10.1.2
- Potable-water sampling to confirm no migration of radiological and/or nonradiological contamination into the site's drinking water supply.
- WNDNKMS** Potable water sampled at the maintenance shop in order to monitor a point that is at an intermediate distance from the point of potable water generation and that is used heavily by site personnel.
- WNDNKMP** Same rationale as **WNDNKMS** but sampled at the break room sink.
- WNDNKEL** Potable water sampled at the Environmental Laboratory.
- WNDNKUR** Sampled at the utility room potable water storage tank before the site drinking water distribution system. Sample location is entry point EP-1.

- Sampling locations are within the site facilities and are not detailed on figures.

**2002 Monitoring Program  
Environmental Surveillance**

**On-Site Groundwater**

Sample Location Code	Monitoring/Reporting Requirements	Sampling Type/Medium	Collection Frequency	Total Annual Sample Collections	Analyses Performed/ Composite Frequency
<b>Low-Level Waste Treatment Facility (SSWMU #1)</b>					
103 104 C 105 C 106 107 108 110 111 116 U 8604 C 8605	Groundwater monitoring points around site super solid waste management units (SSWMUs)  Reported in: <ul style="list-style-type: none"><li>ASER</li><li>Quarterly Groundwater Reports</li></ul>	Grab liquid	→ 4 times per year (generally)*	→ 4 each well (generally)*	→ Gross alpha, gross beta, H-3 *
		Direct field measurement of sampled water	→ Each sampling event*	→ Twice each sampling event	→ Conductivity, pH
<b>Miscellaneous Small Units (SSWMU #2)</b>					
201 U 204 205 206 C 208					
<b>Liquid Waste Treatment System (SSWMU #3)</b>					
301 B 302 U					

NOTE: "U" designates upgradient, "B" designates background, and "C" designates crossgradient wells. The remainder are downgradient.

\* Sampling frequency and analytes vary from point to point. See Table 4-1 (p. 4-6) for a summary listing of all monitored analytes. See Table E-1 (Appendix E [p. E-3]) for a listing of analytes monitored at each location. See Appendix E for results from each location.

## Sampling Rationale

---

<b>On-Site Groundwater</b>	DOE Order 5400.1, IV.9; DOE/EH-0173T, 5.10.1.3; 40 CFR Parts 264 and 265, Subpart F  The on-site WVDP groundwater monitoring program provides for the determination of water quality, focusing on radiological and chemical surveillance of both active and inactive super solid waste management units (SSWMUs). In addition, using wells situated hydraulically upgradient (background) and downgradient of SSWMUs allows both detection of groundwater contamination and evaluation of the effects associated with the individual SSWMUs. Groundwater protection was addressed in the Groundwater Protection Management Program Plan, WVDP-091. Groundwater monitoring was detailed in the Groundwater Monitoring Plan, WVDP-239.
<b>SSWMU #1</b>	Low-level waste treatment facilities, including four active lagoons – lagoons 2, 3, 4, and 5 – and an inactive, filled-in lagoon – lagoon 1.
<b>SSWMU #2</b>	Miscellaneous small units, including the sludge pond, the solvent dike, the paper incinerator, the equalization basin, and the kerosene tank.
<b>SSWMU #3</b>	Liquid waste treatment system containing effluent from the supernatant treatment system.

- Sampling locations are shown on Figures A-6 and A-7 (pp. A-8 and A-9).

**2002 Monitoring Program  
Environmental Surveillance**

**On-Site Groundwater**

<u>Sample Location Code</u>	<u>Monitoring/Reporting Requirements</u>	<u>Sampling Type/Medium</u>	<u>Collection Frequency</u>	<u>Total Annual Sample Collections</u>	<u>Analyses Performed/ Composite Frequency</u>
<b>HLW Storage and Processing Tank</b> <i>(SSWMU #4)</i>  401 B 402 U 403 U 405 C 406 408 409	Groundwater monitoring points around site super solid waste management units (SSWMUs)  Reported in: <ul style="list-style-type: none"> <li>• ASER</li> <li>• Quarterly Groundwater Reports</li> </ul>	Grab liquid →  Direct field measurement of sampled water →	4 times per year (generally)* →  Each sampling event* →	4 each well (generally)* →  Twice each sampling event →	Gross alpha, gross beta, H-3 * →  Conductivity, pH →
<b>Maintenance Shop Leach Field</b> <i>(SSWMU #5)</i>  501 U 502					
<b>Low-Level Waste Storage Area</b> <i>(SSWMU #6)</i>  602A 604 605 8607 U 8609 U					
<b>Chemical Process Cell Waste Storage Area</b> <i>(SSWMU #7)</i>  704 706 B 707 C					

NOTE: "U" designates upgradient, "B" designates background, and "C" designates crossgradient wells. The remainder are downgradient.

\* Sampling frequency and analytes vary from point to point. See Table 4-1 (p. 4-6) for a summary listing of all monitored analytes. See Table E-1 (Appendix E [p. E-3]) for a listing of analytes monitored at each location. See Appendix E for results from each location.



## Sampling Rationale

---

- On-Site Groundwater** DOE Order 5400.1, IV.9; DOE/EH-0173T, 5.10.1.3; 40 CFR Parts 264 and 265, Subpart F
- The on-site WVDP groundwater monitoring program provides for the determination of water quality, focusing on radiological and chemical surveillance of both active and inactive super solid waste management units (SSWMUs). In addition, using wells situated hydraulically upgradient (background) and downgradient of SSWMUs allows both detection of groundwater contamination and evaluation of the effects associated with the individual SSWMUs. Groundwater protection was addressed in the Groundwater Protection Management Program Plan, WVDP-091. Groundwater monitoring was detailed in the Groundwater Monitoring Plan, WVDP-239.
- SSWMU #4** High-level waste storage and processing area, including the high-level radioactive waste tanks, the supernatant treatment system, and the vitrification facility.
- SSWMU #5** Maintenance shop sanitary leach field, formerly used by NFS and the WVDP to process domestic sewage generated by the maintenance shop.
- SSWMU #6** Low-level waste storage area; includes metal and fabric structures housing low-level radioactive waste being stored for future disposal.
- SSWMU #7** Chemical process cell (CPC) waste storage area, which contains packages of pipes, vessels, and debris from decontamination and cleanup of the chemical process cell in the former reprocessing plant.

- Sampling locations are shown on Figures A-6 and A-7 (pp. A-8 and A-9).

## 2002 Monitoring Program Environmental Surveillance

### On-Site Groundwater

Sample Location Code	Monitoring/Reporting Requirements	Sampling Type/Medium	Collection Frequency	Total Annual Sample Collections	Analyses Performed/ Composite Frequency
<b>Construction and Demolition Debris Landfill (CDDL)</b> (SSWMU #8)					
801 U 802 803 804 8603 U 8612	Groundwater monitoring points around site super solid waste management units (SSWMUs)	Grab liquid	→ 4 times per year (generally)*	→ 4 each well (generally)*	→ Gross alpha, gross beta, H-3*
<b>NRC-Licensed Disposal Area (NDA)</b> (SSWMU #9)					
901 U 902 U 903 906 908 U 909 910 8610 8611 NDATR	Reported in: <ul style="list-style-type: none"><li>• ASER</li><li>• Quarterly Ground-water Reports</li></ul>	Direct field measurement of sampled water	→ Each sampling event*	→ Twice each sampling event	→ Conductivity, pH
<b>IRTS Drum Cell</b> (SSWMU #10)					
1005 U 1006 1007 1008b B 1008c B					

NOTE: "U" designates upgradient, "B" designates background, and "C" designates crossgradient wells. The remainder are downgradient.

\* Sampling frequency and analytes vary from point to point. See Table 4-1 (p. 4-6) for a summary listing of all monitored analytes. See Table E-1 (Appendix E [p. E-3]) for a listing of analytes monitored at each location. See Appendix E for results from each location.

## Sampling Rationale

---

<b>On-Site Groundwater</b>	DOE Order 5400.1, IV.9; DOE/EH-0173T, 5.10.1.3; 40 CFR Parts 264 and 265, Subpart F  The on-site WVDP groundwater monitoring program provides for the determination of water quality, focusing on radiological and chemical surveillance of both active and inactive super solid waste management units (SSWMUs). In addition, using wells situated hydraulically upgradient (background) and downgradient of SSWMUs allows both detection of groundwater contamination and evaluation of the effects associated with the individual SSWMUs. Groundwater protection was addressed in the Groundwater Protection Management Program Plan, WVDP-091. Groundwater monitoring was detailed in the Groundwater Monitoring Plan, WVDP-239.
<b>SSWMU #8</b>	The construction and demolition debris landfill (CDDL); used by NFS and the WVDP to dispose of nonhazardous and nonradioactive materials.
<b>SSWMU #9</b>	The NRC-licensed disposal area (NDA); contains radioactive wastes generated by NFS and the WVDP. The NDA is bounded on its downgradient (northwest and northeast) perimeters by the interceptor trench, which is sampled at monitoring point NDATR.
<b>SSWMU #10</b>	The integrated radioactive waste system (IRTS) treatment drum cell; stores cement-stablized low-level radioactive waste.

- Sampling locations are shown on Figures A-6 through A-8 (pp. A-8 through A-10).

**2002 Monitoring Program  
Environmental Surveillance**

**On-Site Groundwater and Seeps**

Sample Location Code	Monitoring/Reporting Requirements	Sampling Type/Medium	Collection Frequency	Total Annual Sample Collections	Analyses Performed/Composite Frequency
<b>State-Licensed Disposal Area</b> (SSWMU #11)*					
1101a U 1101b U 1101c U 1102a 1102b 1103a 1103b 1103c 1104a 1104b 1104c 1105a 1105b 1106a U 1106b U 1107a 1108a U 1109a U 1109b U 1110a 1111a	Groundwater monitoring points around site super solid waste management units (SSWMUs)  Reported in: <ul style="list-style-type: none"><li>ASER</li></ul>	Grab liquid →  Grab liquid →	Semiannual →  Annual →	2 each well →  1 each well →	→ Gross alpha/beta, H-3, pH, conductivity, turbidity  → Gamma scan, beta-emitters (C-14, Sr-90, Tc-99, I-129), VOCs
<b>North Plateau Seeps</b> (Not in a SSWMU)					
GSEEP SP04 SP06 SP11 SP12	Groundwater seepage points along the northeastern edge of the north plateau  Reported in: <ul style="list-style-type: none"><li>ASER</li><li>Quarterly Groundwater Reports</li></ul>	Grab liquid →  Direct field measurement of sampled water →	Semiannual (Quarterly at GSEEP) →  Semiannual (Quarterly at GSEEP) →	2 each seep (4 at GSEEP) →  2 each seep (4 at GSEEP) →	→ Gross alpha/beta, H-3, and VOCs at GSEEP and SP12  → pH, conductivity
<b>Miscellaneous Well Points</b> (Not in a SSWMU)					
WP-A WP-C WP-H NB1S (Former Background Well)	Well points down-gradient of main plant and the former sand and gravel unit background well  Reported in: <ul style="list-style-type: none"><li>ASER</li><li>Quarterly Groundwater Reports</li></ul>	Grab liquid →  Direct field measurement of sampled water →	Annual (Quarterly at NB1S) →  Annual (Quarterly at NB1S) →	1 each well (4 at NB1S) →  1 each well (4 at NB1S) →	→ Gross alpha/beta, H-3  → pH, conductivity

NOTE: "U" designates upgradient, "B" designates background, and "C" designates crossgradient wells. The remainder are downgradient.

\* SSWMU #11 is sampled by NYSERDA under a separate program.

## Sampling Rationale

---

<b>On-Site Groundwater</b>	DOE Order 5400.1, IV.9; DOE/EH-0173T, 5.10.1.3; 40 CFR Parts 264 and 265, Subpart F  The on-site WVDP groundwater monitoring program provides for the determination of water quality, focusing on radiological and chemical surveillance of both active and inactive super solid waste management units (SSWMUs). In addition, using wells situated hydraulically upgradient (background) and downgradient of SSWMUs allows both detection of groundwater contamination and evaluation of the effects associated with the individual SSWMUs. Groundwater protection was addressed in the Groundwater Protection Management Program Plan, WVDP-091. Groundwater monitoring was detailed in the Groundwater Monitoring Plan, WVDP-239.
<b>SSWMU #11</b>	The New York State-licensed disposal area (SDA) was operated by NFS as a commercial low-level disposal facility; it also received wastes from NFS reprocessing operations.
<b>North Plateau Seeps</b>	Monitor groundwater emanating from the ground surface along the edge of the site's north plateau.
<b>Well Points</b>	Monitor groundwater of known subsurface contamination in the north plateau area. All well points are downgradient of the main plant.
<b>WNWNB1S</b>	Former background well on the north plateau.

- Sampling locations are shown on Figures A-6 through A-8 (pp. A-8 through A-10).

## 2002 Monitoring Program Environmental Surveillance

### Off-Site Surface Water

Sample Location Code	Monitoring/Reporting Requirements	Sampling Type/Medium	Collection Frequency	Total Annual Sample Collections	Analyses Performed/ Composite Frequency
<b>WFBCTCB*</b> <i>Buttermilk Creek Upstream of Confluence With Cattaraugus Creek at Thomas Corners Road</i>	Restricted surface waters receiving plant effluents  Reported in: <ul style="list-style-type: none"><li>• MTAR</li><li>• ASER</li></ul>	Timed continuous composite liquid	→ Weekly	→ 52	→ pH, conductivity
				Weekly samples composited to 12	→ Monthly composite for gross alpha/beta, H-3
				Weekly samples composited to 4	→ Quarterly composite for gamma isotopic and Sr-90
<b>WFFELBR*</b> <i>Cattaraugus Creek at Felton Bridge</i>	Unrestricted surface waters receiving plant effluents  Reported in: <ul style="list-style-type: none"><li>• MTAR</li><li>• ASER</li></ul>	Timed continuous composite liquid	→ Weekly	→ 52	→ Gross alpha/beta, H-3, pH
				Weekly samples composited to 12	→ Flow-weighted monthly composite for gamma isotopic, H-3, Sr-90, and gross alpha/beta
<b>WFBCBKG*</b> <i>Buttermilk Creek Near Fox Valley (Background)</i>	Unrestricted surface water, background  Reported in: <ul style="list-style-type: none"><li>• MTAR</li><li>• ASER</li><li>• Reported to NYSERDA</li></ul>	Timed continuous composite liquid	→ Weekly	→ 52	→ pH, conductivity
				Weekly samples composited to 12	→ Monthly composite for gross alpha/beta, H-3
				Weekly samples composited to 4	→ Quarterly composite for gamma isotopic, C-14, Sr-90, Tc-99, I-129, U-232, U-233/234, U-235/236, U-238, total U, Pu-238, Pu-239/240, Am-241
				Grab liquid → Semiannual → 2	→ NPOC, TOX, Ca, Mg, Na, K, Ba, Mn, Fe, Cl, SO <sub>4</sub> , NO <sub>3</sub> +NO <sub>2</sub> -N, F, HCO <sub>3</sub> , CO <sub>3</sub>
<b>WFBIGBR</b> <i>Cattaraugus Creek at Bigelow Bridge (Background)</i>	Unrestricted surface water, background  Reported in: <ul style="list-style-type: none"><li>• MTAR</li><li>• ASER</li></ul>	Grab liquid	→ Monthly	→ 12	→ Gross alpha/beta, H-3, Sr-90, gamma isotopic, pH

\* Monthly composites are also sent to NYSDOH.

## Sampling Rationale

---

**WFBCTCB** DOE/EH-0173T, 5.10.1.1

Buttermilk Creek is the surface water that receives all WVDP effluents. **WFBCTCB** monitors the potential influence of WVDP drainage into Buttermilk Creek upstream of Buttermilk Creek's confluence with Cattaraugus Creek.

**WFFELBR** DOE/EH-0173T, 5.10.1.1

Because Buttermilk Creek empties into Cattaraugus Creek, **WFFELBR** monitors the potential influence of WVDP drainage into Cattaraugus Creek directly downstream of the Cattaraugus Creek confluence with Buttermilk Creek.

**WFBCBKG** DOE/EH-0173T, 5.10.1.1

Monitors background conditions of Buttermilk Creek upstream of the WVDP; allows comparison to downstream conditions.

**WFBIGBR** DOE/EH-0173T, 5.10.1.1

Monitors background conditions of Cattaraugus Creek at Bigelow Bridge, upstream of the WVDP; allows comparison to downstream conditions.

■ Sampling locations are shown on Figure A-3 (p. A-5).

**2002 Monitoring Program  
Environmental Surveillance**

**Off-Site Drinking Water**

<u>Sample Location Code</u>	<u>Monitoring/Reporting Requirements</u>	<u>Sampling Type/Medium</u>	<u>Collection Frequency</u>	<u>Total Annual Sample Collections</u>	<u>Analyses Performed/ Composite Frequency</u>
<b>WFWEL Series</b> <i>Wells Outside the WNYNSC Perimeter But Near the WVDP</i>					
<b>WFWEL01</b> <i>3.0 km West-Northwest</i>	Drinking water supply; groundwater near facility*  Reported in: <ul style="list-style-type: none"><li>• MTAR</li><li>• ASER</li></ul>	Grab liquid	→ Annual	→ 1 each location	→ Gross alpha/beta, H-3, gamma isotopic
<b>WFWEL02</b> <i>1.5 km Northwest</i>					
<b>WFWEL03</b> <i>3.5 km Northwest</i>		Direct field measurement of sampled water	→ Annual	→ 1 each location	→ pH, conductivity
<b>WFWEL04</b> <i>3.0 km Northwest</i>					
<b>WFWEL05</b> <i>2.5 km Southwest</i>					
<b>WFWEL06</b> <i>(Background) 29 km South</i>					
<b>WFWEL07</b> <i>4.4 km North-Northeast</i>					
<b>WFWEL08</b> <i>2.5 km East-Northeast</i>					
<b>WFWEL09</b> <i>3.0 km Southeast</i>					
<b>WFWEL10</b> <i>7.0 km North</i>					

\* No drinking water wells are located in hydrogeological units affected by site activity.



## Sampling Rationale

---

**Off-Site** DOE 5400.1, IV.9; DOE/EH-0173T, 5.10.1.2

**Drinking Water**

**WFWEL Series** Eight of the ten listed off-site private residential drinking water wells represent the nearest unrestricted uses of groundwater close to the WVDP. The ninth sample (**WFWEL10**) is taken from a public water supply from deep wells. The tenth drinking water well, **WFWEL06**, is located 29 kilometers south of the Project and is considered a background drinking water source.

- Sampling locations are shown on Figures A-9, A-12, and A-13 (pp. A-11, A-14, and A-15).

## 2002 Monitoring Program Environmental Surveillance

### Off-Site Air

Sample Location Code	Monitoring/Reporting Requirements	Sampling Type/Medium	Collection Frequency	Total Annual Sample Collections	Analyses Performed/ Composite Frequency	
<b>AFFXVRD</b> <i>3.0 km South-Southeast at Fox Valley</i>	Particulate air samples around WNYNSC perimeter  Reported in:  <ul style="list-style-type: none"> <li>• MTAR</li> <li>• ASER</li> </ul>	Continuous air particulate filter	→ Weekly	→ 52 each location	→ Gross alpha/beta, flow	
<b>AFTCORD</b> <i>3.7 km North-Northwest at Thomas Corners Road</i>				Weekly filters composited to 4 each location	→ Quarterly composite for Sr-90, gamma isotopic	
<b>AFRT240*</b> <i>2.0 km Northeast on Route 240</i>						In addition, quarterly composite at
<b>AFSPRVL</b> <i>9.4 km North at Springville</i>						AFRSPRD and
<b>AFWEVAL</b> <i>6.2 km South-Southeast at West Valley</i>						AFGRVAL for
<b>AFNASHV</b> <i>39.8 km West at Village of Nashville, Town of Hanover (Background)</i>			Continuous desiccant column for water vapor collection at	→ Weekly	→ 52 each location	→ H-3
<b>AFBOEHN</b> <i>2.3 km Southwest on Dutch Hill Road</i>			AFRSPRD and			
<b>AFRSPRD</b> <i>1.5 km Northwest on Rock Springs Road</i>			AFGRVAL			
<b>AFGRVAL</b> <i>30.9 km South at Great Valley (Background)</i>		Continuous charcoal cartridge at	→ Monthly	→ 12 composited to 4 each location	→ Quarterly composite for I-129	
<b>AFBLKST</b> <i>Bulk Storage Warehouse 2.2 km East-Southeast at Buttermilk Road</i>		AFRSPRD and				
		AFGRVAL				

\* Filter from duplicate sampler sent to NYSDOH.

## Sampling Rationale

---

<b>AFFXVRD</b>	DOE/EH-0173T, 5.7.4
<b>AFTCORD</b> <b>AFRT240</b>	Air samplers put into service by NFS as part of the site's original monitoring program at perimeter locations chosen to obtain data from places most likely to provide highest concentrations. Choice of location based on meteorological data.
<b>AFSPRVL</b>	DOE/EH-0173T, 5.7.4; DOE/EP-0023, 4.2.3  Off-site (remote) sampler located on private property in a nearby community within 15 kilometers of the site (north).
<b>AFWEVAL</b>	DOE/EH-0173T, 5.7.4; DOE/EP-0023, 4.2.3  Off-site (remote) sampler located in a nearby community within 15 kilometers of the site (southeast).
<b>AFNASHV</b>	DOE/EH-0173T, 5.7.4; DOE/EP-0023, 4.2.3  Off-site (remote) sampler considered representative of natural background radiation. Located 39.8 kilometers west of the site (upwind) on privately owned property.
<b>AFBOEHN</b>	DOE/EH-0173T, 5.7.4; DOE/EP-0023, 4.2.3  Perimeter location chosen to obtain data from the place most likely to provide the highest elevated release concentrations. <b>AFBOEHN</b> is located on NYSERDA property at the perimeter. Choice of location based on meteorological data.
<b>AFRSPRD</b>	DOE/EH-0173T, 5.7.4  Perimeter location chosen to obtain data from the place most likely to provide the highest ground-level release concentrations. <b>AFRSPRD</b> is on WYNNSC property outside the main plant operations fenceline. H-3 and I-129 are sampled here because the sampling trains were easy to incorporate and the location was most likely to receive effluent releases. Choice of location based on meteorological data.
<b>AFGRVAL</b>	DOE/EH-0173T, 5.7.4; DOE/EP-0023, 4.2.3  Off-site (remote) sampler considered representative of natural background radiation. Located on privately owned property 30.9 kilometers south of the site (typically upwind). H-3 and I-129 sampled here also.
<b>AFBLKST</b>	DOE/EH-0173T, 5.7.4  Off-site monitoring of bulk storage warehouse, near the site perimeter.

■ Sampling locations are shown on Figures A-5, A-12, and A-13 (pp. A-7, A-14, and A-15).

## 2002 Monitoring Program Environmental Surveillance

### Fallout, Sediment, and Soil

Sample Location Code	Monitoring/Reporting Requirements	Sampling Type/Medium	Collection Frequency	Total Annual Sample Collections	Analyses Performed/ Composite Frequency
<b>AFDHFOP</b> 2.3 km Southwest  <b>AFFXFOP</b> 3.0 km South-Southeast  <b>AFTCFOP</b> 3.7 km North-Northwest  <b>AF24FOP</b> 2.0 km Northeast  <b>ANRGFOP</b> Rain Gauge On-Site	Collection of fallout particulates and precipitation around the WNYNSC perimeter  Reported in: <ul style="list-style-type: none"> <li>• MTAR</li> <li>• ASER</li> </ul>	Integrated precipitation	Monthly	12 each location	Gross alpha/beta, H-3, pH, gamma isotopic
<b>SF Soil Series</b> Surface Soil at Each of 10 Air Samplers	Long-term fallout accumulation  Reported in: <ul style="list-style-type: none"> <li>• MTAR</li> <li>• ASER</li> </ul>	Surface plug composite soil	Annual	1 each location	Gross alpha/beta, gamma isotopic, Sr-90, Pu-238, Pu-239/240, Am-241 In addition at <b>SFRSPRD</b> , <b>SFBOEHN</b> , and <b>SFGRVAL</b> : U-232, U-233/234, U-235/236, U-238, and total U
<b>SFCCSED</b> Cattaraugus Creek at Felton Bridge  <b>SFSDSED</b> Cattaraugus Creek at Springville Dam  <b>SFBISED</b> Cattaraugus Creek at Bigelow Bridge (Background)  <b>SFTCSED</b> Buttermilk Creek at Thomas Corners Road  <b>SFBCESED</b> Buttermilk Creek at Fox Valley Road (Background)	Deposition in sediment downstream of facility effluents  Reported in: <ul style="list-style-type: none"> <li>• MTAR</li> <li>• ASER</li> </ul>	Grab stream sediment	Annual (Split <b>SFSDSED</b> and <b>SFBCESED</b> with NYSDOH)	1 each location	Gross alpha/beta, gamma isotopic, Sr-90, U-232, U-233/234, U-235/236, U-238, total U, Pu-238, Pu-239/240, Am-241
<b>SN On-Site Soil Series:</b>  <b>SNSW74A</b> (Near WNSW74A)  <b>SNSWAMP</b> (Near WNSWAMP)  <b>SNSP006</b> (Near WNSP006)	Reported in: <ul style="list-style-type: none"> <li>• MTAR</li> <li>• ASER</li> </ul>	Surface plug or grab	Annual	1 each location	Gross alpha/beta, gamma isotopic, Sr-90, U-232, U-233/234, U-235/236, U-238, total U, Pu-238, Pu-239/240, and Am-241, Al, Sb, As, Ba, Be, Cd, Ca, Cr, Co, Cu, Fe, Pb, Mg, Mn, Hg, Ni, K, Se, Ag, Na, Tl, V, Zn

## Sampling Rationale

---

<b>AFDHFOP</b>	DOE/EP-0023, 4.7
<b>AFFXFOP</b>	
<b>AFTCFOP</b>	
<b>AF24FOP</b>	Collection of fallout particles and precipitation around the site perimeter at established air sampling locations: <b>AFDHFOP</b> (Dutch Hill at Boehn Road), <b>AFFXFOP</b> (Fox Valley Road), <b>AFTCFOP</b> (Thomas Corners), <b>AF24FOP</b> (Route 240). Indicates short-term effects.
<b>ANRGFOP</b>	Fallout particles and precipitation collected on-site by the Environmental Laboratory at the rain gauge. Indicates short-term effects.
<b>SF Soil Series</b>	DOE/EH-0173T, 5.9.1
	Off-site soils collected at air sampling locations. <b>SFWEVAL</b> (West Valley), <b>SFFXVRD</b> (Fox Valley Road), <b>SFSPRVL</b> (Springville), <b>SFTCORD</b> (Thomas Corners), <b>SFRT240</b> (Route 240), <b>SFNASHV</b> (Nashville), <b>SFBOEHN</b> (Boehn Road-Dutch Hill), <b>SFGRVAL</b> (Great Valley), <b>SFRSPRD</b> (Rock Springs Road), <b>SFBLKST</b> (bulk storage warehouse): Collection of long-term fallout data at established air sampler locations via soil sampling.
<b>SFCCSED</b>	DOE/EH-0173T, 5.12.1
	Sediment deposition at Cattaraugus Creek at Felton Bridge. Location is first point of public access to Cattaraugus Creek downstream of its confluence with Buttermilk Creek.
<b>SFSDSED</b>	DOE/EH-0173T, 5.12.1
	Sediment deposition in Cattaraugus Creek at Springville Dam. Reservoir provides ideal settling and collection location for sediments downstream of Buttermilk Creek confluence with Cattaraugus Creek. Located downstream of <b>SFCCSED</b> .
<b>SFBISED</b>	DOE/EH-0173T, 5.12.1
	Sediment deposition in Cattaraugus Creek at Bigelow Bridge. Location is upstream of the Buttermilk Creek confluence and serves as the Cattaraugus Creek background location.
<b>SFTCSED</b>	DOE/EH-0173T, 5.12.1
	Sediment deposition in Thomas Corners in Buttermilk Creek immediately downstream of all facility liquid effluents.
<b>SFBCSED</b>	DOE/EH-0173T, 5.12.1
	Sediment deposition in Buttermilk Creek upsteam of facility effluents (background).
<b>SN Soil Series</b>	DOE/EH-0173T, 5.9.1.
	On-site soil. (Samples may be partially composed of sediments.) <b>SNSW74A</b> (surface soil near <b>WNSW74A</b> ), <b>SNSWAMP</b> (surface soil near <b>WNSWAMP</b> ), and <b>SNSP006</b> (surface soil near <b>WNSP006</b> ): Locations to be specifically defined by geographic coordinates. Correspond to site drainage pattern flows (i.e., most likely area of radiological deposition/accumulation).

■ Sampling locations are shown on Figures A-2 through A-5, A-12, and A-13 (pp. A-4 through A-7, A-14, and A-15).

**2002 Monitoring Program  
Environmental Surveillance**

**Off-Site Biological**

Sample Location Code	Monitoring/Reporting Requirements	Sampling Type/Medium	Collection Frequency	Total Annual Sample Collections	Analyses Performed/ Composite Frequency
<b>BFFCATC</b> <i>Fish From Cattaraugus Creek Downstream of Its Confluence With Buttermilk Creek</i>	Fish in waters up- and downstream of facility effluents  Reported in: <ul style="list-style-type: none"> <li>• MTAR</li> <li>• ASER</li> </ul>	Individual collection, biological	→ Semiannual (samples at <b>BFFCATC</b> and <b>BFFCTRL</b> shared with NYSDOH)	→ 20 fish each location	→ Gamma isotopic and Sr-90 in edible portions of each individual fish, % moisture
<b>BFFCATD</b> <i>Fish From Cattaraugus Creek Downstream of the Springville Dam</i>			→ Annual ( <b>BFFCATD</b> only)	→ 10 fish	→ Gamma isotopic and Sr-90 in edible portions of each individual fish, % moisture
<b>BFFCTRL</b> <i>Control Fish Sample From Nearby Stream Not Affected by the WVDP (7 km or More Upstream of Site Effluent Point; Background)</i>					
<b>BFMREED</b> <i>Dairy Farm 3.8 km North-Northwest</i>	Milk from animals foraging at locations near the facility perimeter and at background sites  Milk from animals foraging at background sites  Reported in: <ul style="list-style-type: none"> <li>• MTAR</li> <li>• ASER</li> </ul>	Grab biological	→ Monthly (samples at <b>BFMREED</b> shared with NYSDOH)	→ 12 monthly samples composited to 4 each location	→ Quarterly composite for gamma isotopic, H-3, Sr-90, and I-129
<b>BFMCTLS</b> <i>Control Location 25 km South (Background)</i>					
<b>BFMCTLN</b> <i>Control Location 30 km North (Background)</i>					
<b>BFMWIDR</b> <i>Dairy Farm 3.0 km Southeast</i>	Milk from animals foraging near the site perimeter  Reported in: <ul style="list-style-type: none"> <li>• MTAR</li> <li>• ASER</li> </ul>	Grab biological	→ Annual	→ 1 each location	→ Gamma isotopic, H-3, Sr-90, and I-129
<b>BFMSCHT</b> <i>Dairy Farm 4.8 km South</i>					

## Sampling Rationale

---

<b>BFFCATC</b> <b>BFTCATD</b>	DOE/EH-0173T, 5.11.1.1  Radioactivity may enter a food chain in which fish are a major component and are consumed by the local population.
<b>BFFCTRL</b>	Control fish sample; provide background data for comparison with data from fish caught downstream of facility effluents.
<b>BFMREED</b>	DOE/EH-0173T, 5.8.2.1  Milk is consumed by all age groups and is frequently the most important food that could contribute to the radiation dose. Dairy animals pastured near the site and at two background locations allow adequate monitoring. Control milk samples are collected far from the site to provide background data for comparison with data from near-site milk samples.
<b>BFMWIDR</b> <b>BFMSCHT</b>	Milk from animals foraging around facility perimeter.

- Sampling locations are shown on Figures A-9, A-12, and A-13 (pp. A-11, A-14, and A-15).

## 2002 Monitoring Program Environmental Surveillance

### Off-Site Biological

Sample Location Code	Monitoring/Reporting Requirements	Sampling Type/Medium	Collection Frequency	Total Annual Sample Collections	Analyses Performed/Composite Frequency
<b>BFVNEAR*</b> <i>Nearby Locations</i>  <b>BFVCTRL*</b> <i>Remote Locations (16 km or More From Facility; Background)</i>	Fruit and vegetables grown near facility perimeter, downwind if possible, and at background locations  Reported in: <ul style="list-style-type: none"> <li>• MTAR</li> <li>• ASER</li> </ul>	Grab biological (fruits and vegetables)	→ Annual (at harvest)	→ 3 each (split with NYSDOH)	→ Gamma isotopic and Sr-90 analysis of edible portions, H-3 in free moisture, % moisture
<b>BFHNEAR</b> <i>Forage for Beef Cattle/ Milk Cows From Near-Site Location</i>  <b>BFHCTLS or BFHCTLN</b> <i>Forage for Beef Cattle/ Milk Cows From Control Location South or North (Background)</i>	Forage (hay) grown near facility perimeter, downwind if possible, and at background locations  Reported in: <ul style="list-style-type: none"> <li>• MTAR</li> <li>• ASER</li> </ul>	Grab biological	→ Annual	→ 1 each location	→ Gamma isotopic, Sr-90
<b>BFBNEAR</b> <i>Beef Animal From Nearby Farm in Downwind Direction</i>  <b>BFBCTRL</b> <i>Beef Animal From Control Location 16 km or More From Facility (Background)</i>	Meat (beef foraging near facility perimeter, downwind if possible, and a background location)  Reported in: <ul style="list-style-type: none"> <li>• MTAR</li> <li>• ASER</li> </ul>	Grab biological	→ Semiannual	→ 2 each location	→ Gamma isotopic and Sr-90 analysis of meat, H-3 in free moisture, % moisture
<b>BFDNEAR</b> <i>Deer in Vicinity of the Site</i>  <b>BFDCTRL</b> <i>Control Deer 16 km or More From the Facility (Background)</i>	Venison (deer foraging near facility perimeter and at background locations)  Reported in: <ul style="list-style-type: none"> <li>• MTAR</li> <li>• ASER</li> </ul>	Individual collection, biological	→ Annual, during hunting season ( <b>BFDNEAR</b> sample split with NYSDOH)  During year as available ( <b>BFDCTRL</b> sample split with NYSDOH)	→ 3  → 3	→ Gamma isotopic and Sr-90 analysis of meat, H-3 in free moisture, % moisture

\* Near-site and control corn, apple, and bean samples are identified specifically as follows: corn = **BFVNEAC** and **BFVCTRC**; apples = **BFVNEAAF** and **BFVCTRA**; beans = **BFVNEAB** and **BFVCTRB**.



## Sampling Rationale

---

<b>BFVNEAR</b>	DOE/EH-0173T, 5.8.2.2  Fruits and vegetables (corn, apples, and beans or leafy vegetables, if available) collected from areas near the site. These samples are collected, if possible, from areas near the site predicted to have worst-case downwind concentrations of radionuclides in air and soil. Sample analysis reflects steady state/chronic uptake or contamination of foodstuffs as a result of site activities. Possible pathway directly to humans or indirectly through animals.
<b>BFVCTRL</b>	DOE/EH-0173T, 5.8.2.2  Fruits and vegetables collected from an area remote from the site. Background fruits and vegetables collected for comparison with near-site samples. Collected in area(s) of no possible site effects.
<b>BFHNEAR</b>	DOE/EH-0173T, 5.8.2.2  Hay collected from area near the site. Same as for near-site fruits and vegetables ( <b>BFVNEAR</b> ). Indirect pathway to humans through animals. Collected from same location as beef or milk sample.
<b>BFHCTLS</b> <b>BFHCTLN</b>	DOE/EH-0173T, 5.8.2.2  Hay collected from areas remote from the site. Background hay collected for comparison with near-site samples. Collected in area(s) of no possible effects from the site.
<b>BFBNEAR</b>	DOE/EH-0173T, 5.8.2.3  Beef collected from animals raised near the site and foraging downwind of the site in areas of maximum probable effects. Following the rationale for vegetable matter collected near the site ( <b>BFVNEAR</b> and <b>BFHNEAR</b> ), edible flesh portion of beef animals is analyzed to determine possible radionuclide content passable directly to humans.
<b>BFBCTRL</b>	DOE/EH-0173T, 5.8.2.3  Beef collected from animals raised far from the site. Background beef collected for comparison with near-site samples. Collected in area(s) of no possible site effects.
<b>BFDNEAR</b>	DOE/EH-0173T, 5.8.3  Venison from near-site deer. Samples are taken from deer killed in collisions with vehicles. Sample rationale is similar to <b>BFBNEAR</b> .
<b>BFDCCTRL</b>	DOE/EH-0173T, 5.8.3  Venison from deer living far from the site. Background deer meat collected for comparison with near-site samples. Collected in area(s) of no possible site effects.

■ Sampling locations are shown on Figures A-9, A-12, and A-13 (pp. A-11, A-14, and A-15).

**2002 Monitoring Program  
Environmental Surveillance**

**Off-Site Direct Radiation**

<u>Sample Location Code</u>	<u>Monitoring/Reporting Requirements</u>	<u>Sampling Type/Medium</u>	<u>Collection Frequency</u>	<u>Total Annual Sample Collections</u>	<u>Analyses Performed/ Composite Frequency</u>
<b>DFTLD Series</b> <i>Thermoluminescent Dosimetry (TLD)</i> <i>Off-Site:</i>  <b>#1-#16</b> <i>Each of 16 Compass Sectors at Nearest Accessible Perimeter Point</i>  <b>#17</b> <i>"5 points" Landfill</i> <i>19.6 km Southwest (Background)</i>  <b>#20</b> <i>1,500 m Northwest (Downwind Receptor)</i>  <b>#21</b> <i>Springville</i> <i>9.4 km North</i>  <b>#22</b> <i>West Valley</i> <i>6.2 km South-Southeast</i>  <b>#23</b> <i>Great Valley</i> <i>30.9 km South (Background)</i>  <b>#37</b> <i>Nashville</i> <i>39.8 km Northwest (Background)</i>  <b>#41</b> <i>Sardinia-Savage Road</i> <i>15.5 km Northeast (Background)</i>	Direct radiation around facility  Reported in: <ul style="list-style-type: none"> <li>• MTAR</li> <li>• ASER</li> </ul>	Integrating TLD	→ Quarterly	→ TLD cards at each of 23 locations collected 4 times per year	→ Quarterly gamma radiation exposure

## Sampling Rationale

---

**Direct Radiation** DOE/EH-0173T, 5.5; DOE/EP-0023, 4.6.3  
**Off-Site**

TLDs offer continuous integrated environmental gamma-ray monitoring and have been deployed systematically about the site. Off-site TLDs are used to verify that site activities have not adversely affected the surrounding environs.

An annual high-pressure ion chamber (HPIC) gamma radiation measurement is completed at all locations in order to confirm TLD measurements.

- Sampling locations are shown on Figures A-11 through A-13 (pp. A-13 through A-15).

**2002 Monitoring Program  
Environmental Surveillance**

**On-Site Direct Radiation**

<u>Sample Location Code</u>	<u>Monitoring/Reporting Requirements</u>	<u>Sampling Type/Medium</u>	<u>Collection Frequency</u>	<u>Total Annual Sample Collections</u>	<u>Analyses Performed/ Composite Frequency</u>
<b>DNTLD Series</b> <i>Thermoluminescent Dosimetry (TLD) On-Site:</i>  <b>#18, #19, #33</b> <i>At Three Corners of the SDA</i>  <b>#24, #26-#32, #34</b> <i>9 TLDS at the Security Fence Around the Site</i>  <b>#35, #36, #38-#40</b> <i>5 TLDS On-Site Near Operational Areas</i>  <b>#25</b> <i>Rock Springs Road 500 m North-Northwest of the Plant</i>  <b>#42</b> <i>SDA T-1 Building</i>  <b>#43</b> <i>SDA west Perimeter Fence</i>	Direct radiation around facility  Reported in: <ul style="list-style-type: none"> <li>• MTAR</li> <li>• ASER</li> </ul>	Integrating TLD	→ Quarterly	→ TLD cards at each of 20 locations collected 4 times per year	→ Quarterly gamma radiation exposure

## Sampling Rationale

---

**Direct Radiation** DOE/EH-0173T, 5.4 and 5.5  
**On-Site**

On-site TLDs monitor waste management units and verify that the potential dose rate to the general public (i.e., at Rock Springs Road) is below 100 mrem/year (1 mSv/year) from site activities.

An annual high-pressure ion chamber (HPIC) gamma radiation measurement is completed at all locations in order to confirm TLD measurements.

Potential TLD sampling locations are continually evaluated with respect to site activities.

- Sampling locations are shown on Figure A-10 (p. A-12).

*This page intentionally left blank*